



Mobile High Pressure Cleaner, electrically-heated FHE 718 MP

► Data Sheet



1.0	Type	FHE 718 MP		
2.0	Capacity			
2.1	Mains connection	400 V 3 AC 50 Hz		
2.2	Nominal consumption	23 kW 31 A		
3.0	High pressure stage			
3.1	Working pressure	180 bar		
3.2	Operating temperature max.	70 °C		
3.3	Warm-up time	6 min.		
3.4	Heat capacity	18 kW		
4.0	Steam stage			
4.1	Working overpressure	60 - 180 bar		
4.2	Flow rate	400 - 700 l/h		
4.3	Constant temperature at 700 l/h at a water inlet temperature of 15 °C	40 °C		
4.4	Constant temperature at 400 l/h at a water inlet temperature of 15 °C	55 °C		
4.5	Tenk content	27 l		
5.0	Specification			
5.1	High pressure pump with 3 solid ceramic plungers	Type NP 16/13	Order nr.	7041307000
5.2	Overflow safety valve	Type ULH for TCC	Order nr.	2098952000
5.6	Spray lance for hand socket		Order nr.	2096750000
5.7	with spray lance with hand socket TCC 1		Order nr.	2095950000
5.8	with high pressure flat jet nozzle	Type 2505	Order nr.	7023230000
5.9	with 10 m high pressure hose	Type DN 8	Order nr.	2051560000
5.10	Electrical motor for high pressure pump drive	Performance 4 kW	Order nr.	7041524000
5.11	Connecting cable 5 x 4 mm ²	5 m with mains plug 32 A		
6.0	Dimensions with trolley (LxWxH)	1245x590x845 mm		
7.0	Weight	120 Kg		