



# Mobile High Pressure Cleaner, electrically-heated FHE 718 TCC

## ► Data Sheet



<b>1.0</b>	<b>Type</b>	FHE 718 TCC		
<b>2.0</b>	<b>Capacity</b>			
2.1	Mains connection	400 V 3 AC 50 Hz		
2.2	Nominal consumption	23 kW 31 A		
2.3	Heat capacity	18 kW		
2.4	Tank content	27 l		
2.5	Warm-up time	6 minutes		
2.6	at a water inlet temperature of 15°C			
2.6	Connecting cable 4 x 1.5 mm <sup>2</sup>	5 m with mains plug		
<b>3.0</b>	<b>High pressure stage</b>			
3.1	Working pressure	180 bar		
3.2	Flow rate	700 l/h		
3.3	Operating temperature	40 °C		
	at a water inlet temperature of 15°C			
<b>4.0</b>	<b>Low pressure stage</b>			
4.1	Working pressure	60 bar		
4.2	Flow rate	400 l/h		
4.3	Operating temperature	55 °C		
	at a water inlet temperature of 15 °C			
<b>5.0</b>	<b>Specification</b>			
5.1	High pressure pump with 3 solid ceramic plungers	Type NP 10/11	Order nr.	7041056000
5.2	Overflow safety valve	Type UL 250 HF	Order nr.	2073890000
5.3	Spray lance with plug nipple		Order nr.	1508023
5.4	Spray gun TCC with plug-in coupling		Order nr.	1508026
5.5	High pressure flat jet nozzle	Type 25035	Order nr.	7040692000
5.6	10 m high pressure hose		Order nr.	2051560000
5.7	Electrical motor 4 kW		Order nr.	7041524000
5.8	with high pressure flat jet nozzle	Type 2505	Order nr.	7023230000
5.9	with 10 m high pressure hose	Type DN 8	Order nr.	2051560000
5.10	Electrical motor for high pressure pump drive	Performance 4 kW	Order nr.	7041524000
5.11	Connecting cable 5 x 4 mm <sup>2</sup>	5 m with mains plug		
		32 A		
<b>6.0</b>	<b>Dimensions with trolley (LxWxH)</b>	1245 x 590 x 845 mm		
<b>7.0</b>	<b>Weight</b>	120 kg		

\* EU declaration of conformity updated by the TÜV Hessen

subject to change without prior notice